## **SAFETY DATA SHEET**

Acetylene



## Section 1. Identification

: Acetylene
: acetylene
: Ethyne; Ethine; Narcylen; C2H2; Acetylen; UN 1001; Vinylene
: Synthetic/Analytical chemistry.
: Ethyne; Ethine; Narcylen; C2H2; Acetylen; UN 1001; Vinylene
: 001001
: The Aero ALL-GAS Company 3150 Main Street Hartford, CT 06120 ph:(860) 278-AERO fax:(860) 527-AERO
: 1-800-424-9300 Chemtrec

## Section 2. Hazards identification

Classification of the substance or mixture: FLAMMABLE GASES - Category GASES UNDER PRESSURE - CoGHS label elements Hazard pictograms:Signal word Hazard statements:Contains gas under pressure; may May displace oxygen and cause ra May displace oxygen and cause ra Contains gas under pressure; may May displace oxygen and cause ra Extremely flammable gas. Contains gas under pressure; may May displace oxygen and cause ra Precautionary statementsPrecautionary statements:Read and follow all Safety Data SI Keep out of reach of children. If m label at hand. Close valve after ea cylinder pressure. Do not open va Fusible plugs in top, bottom, or va discharge at pressures above 15p the piping. Use only equipment of suspected leak area with caution.Prevention:Never Put cylinders into unventilat heat, sparks, open flames and hol or in a well ventilated place.	
substance or mixture       GASES UNDER PRESSURE - Color         GHS label elements       Hazard pictograms         Hazard pictograms       :         Signal word       :         Hazard statements       :         Danger       :         Extremely flammable gas.       Contains gas under pressure; may May displace oxygen and cause rates         Precautionary statements       :         General       :         Read and follow all Safety Data SI Keep out of reach of children. If m label at hand. Close valve after eacylinder pressure. Do not open vare usible plugs in top, bottom, or vard ischarge at pressures above 15p the piping. Use only equipment of suspected leak area with caution.         Prevention       :         Never Put cylinders into unventilated heat, sparks, open flames and hol or in a well ventilated place.	us by the OSHA Hazard Communication Standard
GHS label elements Hazard pictograms::Hazard pictograms::Signal word Hazard statements:Danger :Extremely flammable gas. Contains gas under pressure; may May displace oxygen and cause ra May displace oxygen and cause ra :Precautionary statements General:Read and follow all Safety Data SI Keep out of reach of children. If m label at hand. Close valve after ea cylinder pressure. Do not open va Fusible plugs in top, bottom, or va discharge at pressures above 15p the piping. Use only equipment of suspected leak area with caution.Prevention:Never Put cylinders into unventilat heat, sparks, open flames and hol or in a well ventilated place.	
Hazard pictograms:Signal word Hazard statements:Danger :Extremely flammable gas. Contains gas under pressure; may May displace oxygen and cause ray May displace oxygen and cause ray is recent to freach of children. If m label at hand. Close valve after eacylinder pressure. Do not open va Fusible plugs in top, bottom, or va discharge at pressures above 15p the piping. Use only equipment of suspected leak area with caution.Prevention:Prevention:Never Put cylinders into unventilat heat, sparks, open flames and hod or in a well ventilated place.	ipressed gas
Signal word Hazard statements: DangerBere Contains gas under pressure; may May displace oxygen and cause ray May displace oxygen and cause ray Bereautionary statementsPrecautionary statements General: Read and follow all Safety Data SI Keep out of reach of children. If m label at hand. Close valve after ea cylinder pressure. Do not open va Fusible plugs in top, bottom, or va discharge at pressures above 15p the piping. Use only equipment of suspected leak area with caution.Prevention: Never Put cylinders into unventilat heat, sparks, open flames and hod or in a well ventilated place.	
Hazard statements: Extremely flammable gas. Contains gas under pressure; may May displace oxygen and cause ray May displace oxygen and cause ray extended and follow all Safety Data SI Keep out of reach of children. If m label at hand. Close valve after eacylinder pressure. Do not open va Fusible plugs in top, bottom, or va discharge at pressures above 15p the piping. Use only equipment of suspected leak area with caution.Prevention: Never Put cylinders into unventilat heat, sparks, open flames and hod or in a well ventilated place.	
Precautionary statementsGeneral: Read and follow all Safety Data SI Keep out of reach of children. If m label at hand. Close valve after ea cylinder pressure. Do not open va Fusible plugs in top, bottom, or va discharge at pressures above 15p the piping. Use only equipment of suspected leak area with caution.Prevention: Never Put cylinders into unventilat heat, sparks, open flames and hod or in a well ventilated place.	
<ul> <li>General</li> <li>Read and follow all Safety Data SI Keep out of reach of children. If m label at hand. Close valve after eacylinder pressure. Do not open va Fusible plugs in top, bottom, or va discharge at pressures above 15p the piping. Use only equipment of suspected leak area with caution.</li> <li>Prevention</li> <li>Never Put cylinders into unventilat heat, sparks, open flames and hot or in a well ventilated place.</li> </ul>	
<ul> <li>Keep out of reach of children. If m label at hand. Close valve after ea cylinder pressure. Do not open va Fusible plugs in top, bottom, or va discharge at pressures above 15p the piping. Use only equipment of suspected leak area with caution.</li> <li>Prevention</li> <li>Never Put cylinders into unventilat heat, sparks, open flames and hot or in a well ventilated place.</li> </ul>	
heat, sparks, open flames and hol or in a well ventilated place.	eets (SDS'S) before use. Read label before use. dical advice is needed, have product container or h use and when empty. Use equipment rated for re until connected to equipment prepared for use. e melt at 98°C to 107°C (208°F to 224°F). Do not g (103kpa). Use a back flow preventative device in ompatible materials of construction. Approach
Response	d areas of passenger vehicles. Keep away from urfaces No smoking. Use and store only outdoors
Response: Leaking gas fire: Do not extinguish ignition sources if safe to do so.	unless leak can be stopped safely. Eliminate all
Date of issue/Date of revision       : 04/14/2015       Date of previous issue	: 9/29/2014. Version : 0.03 1/12

## Section 2. Hazards identification

Section 3 Composition/information on ingradiants		
Hazards not otherwise classified	<ul> <li>In addition to any other important health or physical hazards, this product may displace oxygen and cause rapid suffocation.</li> </ul>	
Disposal	: Not applicable.	
Storage	<ul> <li>Protect from sunlight. Protect from sunlight when ambient temperature exceeds 52°C/125°F. Store in a well-ventilated place.</li> </ul>	

### Section 3. Composition/information on ingredients

Substance/mixture	: Substance
Chemical name	: acetylene
Other means of identification	: Ethyne; Ethine; Narcylen; C2H2; Acetylen; UN 1001; Vinylene

#### **CAS number/other identifiers**

CAS number	: 74-86-2		
Product code	: 001001		
Ingredient name		%	CAS number
acetylene		100	74-86-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. To avoid the risk of static discharges and gas ignition, soak contaminated clothing thoroughly with water before removing it. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: As this product is a gas, refer to the inhalation section.
Most important symptoms	effects, acute and delayed
Potential acute health effe	ects
Eye contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Frostbite	: Try to warm up the frozen tissues and seek medical attention.

**Ingestion** : As this product is a gas, refer to the inhalation section.

#### Over-exposure signs/symptoms

Date of issue/Date of revision         : 04/14/2015         Date of previous issue	e : 9/29/2014. Version	: 0.03 2/12
--	------------------------	-------------

## Section 4. First aid measures

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

## Indication of immediate medical attention and special treatment needed, if necessaryNotes to physician: Treat symptomatically. Contact poison treatment specialist immediately if large<br/>quantities have been ingested or inhaled.Specific treatments: No specific treatment.Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. It may<br/>be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### See toxicological information (Section 11)

Section 5. Fire-fighting measures		
Extinguishing media		
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	: None known.	
Specific hazards arising from the chemical	: Contains gas under pressure. Extremely flammable gas. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.	
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. If involved in fire, shut off flow immediately if it can be done without risk. If this is impossible, withdraw from area and allow fire to burn. Fight fire from protected location or maximum possible distance. Eliminate all ignition sources if safe to do so.	
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.	

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	Accidental releases pose a serious fire or explosion hazard. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non- emergency personnel".

Date of issue/Date of revision	:04/14/2015	Date of previous issue	: 9/29/2014.	Version : 0.03	3/12
--------------------------------	-------------	------------------------	--------------	----------------	------

## Section 6. Accidental release measures

Environmental precautions	: Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ntainment and cleaning up
Small spill	: Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment.
Large spill	: Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8). Contains gas under pressure. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardou. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement.	JS.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.	e
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Eliminate all ignition sources. Keep containe tightly closed and sealed until ready for use. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52 °C (125 °F).	۲

## Section 8. Exposure controls/personal protection

#### Control parameters

#### **Occupational exposure limits**

Ingredient name	Exposure limits
acetylene	NIOSH REL (United States, 1/2013). CEIL: 2662 mg/m <sup>3</sup> CEIL: 2500 ppm

## Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Date of issue/Date of revision	:04/14/2015	Date of previous issue	: 9/29/2014.	Version	:0.03	4/12
--------------------------------	-------------	------------------------	--------------	---------	-------	------

## Section 8. Exposure controls/personal protection

	· · · · · · · · · · · · · · · · · · ·
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measu	res
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section 9. Physical and chemical properties

Appearance					
Physical state	: Gas.				
Color	: Colorless.				
Molecular weight	: 26.04 g/mole				
Molecular formula	: C2-H2				
Melting/freezing point	: -81°C (-113.8°F)				
Critical temperature	: 35.25°C (95.5°F)				
Odor	: Mild. Ethereal.				
Odor threshold	: Not available.				
рН	: Not available.				
Flash point	: Closed cup: -18.15°C (-0.67°F)				
Burning time	: Not applicable.				
Burning rate	: Not applicable.				
Date of issue/Date of revision	: 04/14/2015 Date of previous issue : 9/29/2014. Version : 0.03	5/12			

## Section 9. Physical and chemical properties

	• •
Evaporation rate	: Not available.
Flammability (solid, gas)	: Extremely flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and oxidizing materials.
Lower and upper explosive (flammable) limits	: Lower: 2.3% Upper: 100%
Vapor pressure	: 635 (psig)
Vapor density	: 0.907 (Air = 1)
Specific Volume (ft <sup>3</sup> /lb)	: 14.7058
Gas Density (lb/ft <sup>3</sup> )	: 0.0691
Relative density	: Not applicable.
Solubility	: Not available.
Solubility in water	: 1.2 g/l
Partition coefficient: n- octanol/water	: 0.37
Auto-ignition temperature	: 305°C (581°F)
Decomposition temperature	: Not available.
SADT	: Not available.
Viscosity	: Not applicable.

## Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.	
Chemical stability	: The product is stable.	
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.	
Incompatibility with various substances	: Extremely reactive or incompatible with the following materials: oxidizing materials.	
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.	ĺ

Hazardous polymerization : Under normal conditions of storage and use, hazardous polymerization will not occur.

## Section 11. Toxicological information

# Information on toxicological effects Acute toxicity Not available. Irritation/Corrosion Not available.

**Sensitization** 

Date of issue/Date of revision

e : 9/29/2014.

Version : 0.03

## Section 11. Toxicological information

Not available.

**Mutagenicity** 

Not available.

#### **Carcinogenicity**

Not available.

#### Reproductive toxicity

Not available.

#### Teratogenicity

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure) Not available.

#### Aspiration hazard

Not available.

Information on the likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	Contact with rapidly expanding gas may cause burns or frostbite.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Contact with rapidly expanding gas may cause burns or frostbite.
Ingestion	:	As this product is a gas, refer to the inhalation section.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Delayed and immediate effec	ts	and also chronic effects from shor	t and long term exposi	<u>ure</u>	
<u>Short term exposure</u>					
Potential immediate effects	:	Not available.			
Potential delayed effects	:	Not available.			
<u>Long term exposure</u>					
Potential immediate effects	:	Not available.			
Potential delayed effects	:	Not available.			
Potential chronic health effe	ect	2			
Not available.					
General	:	No known significant effects or critic	al hazards.		
Carcinogenicity	:	No known significant effects or critic	al hazards.		
Date of issue/Date of revision		: 04/14/2015 Date of previous issue	: 9/29/2014.	Version	:0.03

7/12

## Section 11. Toxicological information

Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

#### Numerical measures of toxicity

Acute toxicity estimates

Not available.

## Section 12. Ecological information

#### **Toxicity**

Not available.

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
acetylene	0.37	-	low

#### Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

**Other adverse effects** 

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Empty ALL-GAS owned pressure vessels should be returned to ALL-GAS. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Date of issue/Date of revision	:04/14/2015	Date of previous issue	: 9/29/2014.	Version : 0.03	8/12

## Section 14. Transport information

	•				
	DOT	TDG	Mexico	IMDG	IATA
UN number	UN1001	UN1001	UN1001	UN1001	UN1001
UN proper shipping name	ACETYLENE, DISSOLVED	ACETYLENE, DISSOLVED	ACETYLENE, DISSOLVED	ACETYLENE, DISSOLVED	ACETYLENE, DISSOLVED
Transport hazard class(es)	2.1	2.1	2.1	2.1	2.1
Packing group	-	-	-	-	-
Environment	No.	No.	No.	No.	No.
Additional information	Limited quantity Yes. Packaging instruction Passenger aircraft Quantity limitation: Forbidden. Cargo aircraft Quantity limitation: 15 kg	Explosive Limit and Limited Quantity Index 0 Passenger Carrying Ship Index 75 Passenger Carrying Road or Rail Index Forbidden Special provisions 38, 42	-	-	Passenger and Cargo <u>Aircraft</u> Quantity limitation: 0 Forbidden <u>Cargo Aircraft Only</u> Quantity limitation: 15 kg

"Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product."

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to Annex II of MARPOL 73/78 and the IBC Code

## Section 15. Regulatory information

U.S. Federal regulations	: TSCA 8(a) CDR Exempt/Partial exemption: Not determined
	United States inventory (TSCA 8b): This material is listed or exempted.
	Clean Air Act (CAA) 112 regulated flammable substances: acetylene
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Not listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed
Date of issue/Date of revision	: 04/14/2015 Date of previous issue : 9/29/2014. Version : 0.03 9/12

## Section 15. Regulatory information

#### SARA 302/304

#### **Composition/information on ingredients**

No products were found.

#### SARA 304 RQ

: Not applicable.

#### SARA 311/312 Classification

: Fire hazard Sudden release of pressure

Composition/information on ingredients

Name			Sudden release of pressure		(acute) health	Delayed (chronic) health hazard
acetylene	100	Yes.	Yes.	No.	No.	No.

#### State regulations

otato regulationo		
Massachusetts	1	This material is listed.
New York	1	This material is not listed.
New Jersey	:	This material is listed.
Pennsylvania	:	This material is listed.
Canada inventory	:	This material is listed or exempted.
International regulations		
International lists	:	Australia inventory (AICS): This material is listed or exempted. China inventory (IECSC): This material is listed or exempted. Japan inventory: This material is listed or exempted. Korea inventory: This material is listed or exempted. Malaysia Inventory (EHS Register): Not determined. New Zealand Inventory of Chemicals (NZIoC): This material is listed or exempted. Philippines inventory (PICCS): This material is listed or exempted. Taiwan inventory (CSNN): Not determined.
Chemical Weapons Convention List Schedule I Chemicals	:	Not listed
Chemical Weapons Convention List Schedule II Chemicals	:	Not listed
Chemical Weapons Convention List Schedule III Chemicals	:	Not listed
<u>Canada</u>		
WHMIS (Canada)	:	Class A: Compressed gas. Class B-1: Flammable gas. Class F: Dangerously reactive material. <b>CEPA Toxic substances</b> : This material is not listed. <b>Canadian ARET</b> : This material is not listed. <b>Canadian NPRI</b> : This material is listed. <b>Alberta Designated Substances</b> : This material is not listed. <b>Ontario Designated Substances</b> : This material is not listed. <b>Quebec Designated Substances</b> : This material is not listed.

## Section 16. Other information

#### Canada Label requirements : Class A: Compressed gas.

Class A: Compressed gas. Class B-1: Flammable gas. Class F: Dangerously reactive material.

#### Hazardous Material Information System (U.S.A.)

Flammability	4
Physical hazards	

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

#### National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

<u>History</u>	
Date of printing	: 04/14/2015.
Date of issue/Date of revision	: 10/14/2014.
Date of previous issue	: 9/29/2014.
Version	: 0.03
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United NationsACGIH – American Conference of Governmental Industrial Hygienists AIHA – American Industrial Hygiene Association CAS – Chemical Abstract Services CEPA – Canadian Environmental Protection Act CERCLA – Comprehensive Environmental Response, Compensation, and Liability Act (EPA)
Date of issue/Date of revision	: 04/14/2015 Date of previous issue : 9/29/2014. Version : 0.03 11/12

## Section 16. Other information

CFR - United States Code of Federal Regulations **CPR – Controlled Products Regulations** DSL - Domestic Substances List GWP - Global Warming Potential IARC – International Agency for Research on Cancer ICAO – International Civil Aviation Organisation Inh - Inhalation LC – Lethal concentration LD – Lethal dosage NDSL – Non-Domestic Substances List NIOSH - National Institute for Occupational Safety and Health TDG – Canadian Transportation of Dangerous Goods Act and Regulations TLV – Threshold Limit Value TSCA – Toxic Substances Control Act WEEL – Workplace Environmental Exposure Level WHMIS - Canadian Workplace Hazardous Material Information System : Not available.

#### References

Indicates information that has changed from previously issued version.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

:9/29/2014