# SAFETY DATA SHEET

1-Butene



### Section 1. Identification

GHS product identifier	: 1-Butene
Chemical name	: but-1-ene
Other means of identification	: 1-Butene; Butylene
Product use	: Synthetic/Analytical chemistry.
Synonym SDS #	: 1-Butene; Butylene : 001009
Supplier's details	<ul> <li>The Aero ALL-GAS Co.</li> <li>3150 Main Street</li> <li>Hartford, CT 06120</li> <li>ph:(860) 278-AERO</li> <li>fax:(860) 527-AERO</li> </ul>
Emergency telephone	: 1-800-424-9300 Chemtrec

number (with hours of operation)

### Section 2. Hazards identification

(29 CFR 1910.1200).         Classification of the substance or mixture         Signal word         Hazard pictograms         :       Image: Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation.         Precautionary statements         General         :       Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use Keep out of reach of children. If medical advice is needed, have product container label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use Use a back flow preventative device in the piping. Use only equipment of compatible materials of construction. Approach suspected leak area with caution.         Prevention       : Never Put cylinders into unventilated areas of passenger vehicles. Keep away from heat, sparks, open flames and hot surfaces No smoking. Use and store only out or in a well ventilated place.		
substance or mixture       GASES UNDER PRESSURE - Ćompressed gas         GHS label elements       Hazard pictograms         Hazard pictograms       :         Signal word       :         Hazard statements       :         Extremely flammable gas. Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation.         Precautionary statements       :         Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use Keep out of reach of children. If medical advice is needed, have product container label at hand. Close valve after each use and when empty. Use equipment prepared for use Use a back flow preventative device in the piping. Use only equipment of compatible materials of construction. Approach suspected leak area with caution.         Prevention       :       Never Put cylinders into unventilated areas of passenger vehicles. Keep away from heat, sparks, open flames and hot surfaces No smoking. Use and store only out or in a well ventilated place.         Response       :       Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate al ignition sources if safe to do so.         Storage       :       Protect from sunlight. Protect from sunlight when ambient temperature exceeds 52°C/125'F. Store in a well-ventilated place.         Disposal       :       Not applicable.	OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
GHS label elements         Hazard pictograms         i         iiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiii	Classification of the	: FLAMMABLE GASES - Category 1
Hazard pictograms       :         Signal word       :         Hazard statements       :         Extremely flammable gas. Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation.         Precautionary statements       :         General       :       Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use Keep out of reach of children. If medical advice is needed, have product container label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment of compatib materials of construction. Approach suspected leak area with caution.         Prevention       :       Never Put cylinders into unventilated areas of passenger vehicles. Keep away from heat, sparks, open flames and hot surfaces No smoking. Use and store only out or in a well ventilated place.         Response       :       Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate al ignition sources if safe to do so.         Storage       :       Protect from sunlight. Protect from sunlight when ambient temperature exceeds 52°C/125°F. Store in a well-ventilated place.         Disposal       :       Not applicable.	substance or mixture	GASES UNDER PRESSURE - Compressed gas
Signal word       : Danger         Hazard statements       : Extremely flammable gas. Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation.         Precautionary statements       : Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use Keep out of reach of children. If medical advice is needed, have product container is label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment of compatib materials of construction. Approach suspected leak area with caution.         Prevention       : Never Put cylinders into unventilated areas of passenger vehicles. Keep away from heat, sparks, open flames and hot surfaces No smoking. Use and store only out or in a well ventilated place.         Response       : Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate al ignition sources if safe to do so.         Storage       : Protect from sunlight. Protect from sunlight when ambient temperature exceeds 52°C/125°F. Store in a well-ventilated place.         Disposal       : Not applicable.	GHS label elements	
Hazard statements       : Extremely flammable gas. Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation.         Precautionary statements       : Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use Keep out of reach of children. If medical advice is needed, have product container label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment of compatible materials of construction. Approach suspected leak area with caution.         Prevention       : Never Put cylinders into unventilated areas of passenger vehicles. Keep away from heat, sparks, open flames and hot surfaces No smoking. Use and store only out or in a well ventilated place.         Response       : Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate al ignition sources if safe to do so.         Storage       : Protect from sunlight. Protect from sunlight when ambient temperature exceeds 52°C/125°F. Store in a well-ventilated place.         Disposal       : Not applicable.	Hazard pictograms	
Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation.         Precautionary statements         General       : Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use Keep out of reach of children. If medical advice is needed, have product container label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use Use a back flow preventative device in the piping. Use only equipment of compatib materials of construction. Approach suspected leak area with caution.         Prevention       : Never Put cylinders into unventilated areas of passenger vehicles. Keep away from heat, sparks, open flames and hot surfaces No smoking. Use and store only out or in a well ventilated place.         Response       : Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate al ignition sources if safe to do so.         Storage       : Protect from sunlight. Protect from sunlight when ambient temperature exceeds 52°C/125°F. Store in a well-ventilated place.         Disposal       : Not applicable.	Signal word	: Danger
General: Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use Keep out of reach of children. If medical advice is needed, have product container label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use Use a back flow preventative device in the piping. Use only equipment of compatible materials of construction. Approach suspected leak area with caution.Prevention: Never Put cylinders into unventilated areas of passenger vehicles. Keep away from heat, sparks, open flames and hot surfaces No smoking. Use and store only out or in a well ventilated place.Response: Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate al ignition sources if safe to do so.Storage: Protect from sunlight. Protect from sunlight when ambient temperature exceeds 52°C/125°F. Store in a well-ventilated place.Disposal: Not applicable.	Hazard statements	Contains gas under pressure; may explode if heated.
Keep out of reach of children. If medical advice is needed, have product container label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use Use a back flow preventative device in the piping. Use only equipment of compatible materials of construction. Approach suspected leak area with caution.         Prevention       : Never Put cylinders into unventilated areas of passenger vehicles. Keep away from heat, sparks, open flames and hot surfaces No smoking. Use and store only out or in a well ventilated place.         Response       : Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate al ignition sources if safe to do so.         Storage       : Protect from sunlight. Protect from sunlight when ambient temperature exceeds 52°C/125°F. Store in a well-ventilated place.         Disposal       : Not applicable.	Precautionary statements	
Response       : Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate al ignition sources if safe to do so.         Storage       : Protect from sunlight. Protect from sunlight when ambient temperature exceeds 52°C/125°F. Store in a well-ventilated place.         Disposal       : Not applicable.	General	: Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use a back flow preventative device in the piping. Use only equipment of compatible materials of construction. Approach suspected leak area with caution.
Storage       : Protect from sunlight. Protect from sunlight when ambient temperature exceeds 52°C/125°F. Store in a well-ventilated place.         Disposal       : Not applicable.	Prevention	: Never Put cylinders into unventilated areas of passenger vehicles. Keep away from heat, sparks, open flames and hot surfaces No smoking. Use and store only outdoors or in a well ventilated place.
52°C/125°F. Store in a well-ventilated place.         Disposal       : Not applicable.	Response	<ul> <li>Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so.</li> </ul>
· · · ·	Storage	
Date of issue/Date of revision : 04/21/2015. Date of previous issue : 9/29/2014. Version : 0.04	Disposal	: Not applicable.
	Date of issue/Date of revision	: 04/21/2015. Date of previous issue : 9/29/2014. Version : 0.04 1/12

### Section 2. Hazards identification

Hazards not otherwise	: In addition to any other important health or physical hazards, this product may displace
classified	oxygen and cause rapid suffocation.
	May cause frostbite.

### Section 3. Composition/information on ingredients

Substance/mixture	: Substance
Chemical name	: but-1-ene
Other means of identification	: 1-Butene; Butylene

#### CAS number/other identifiers

CAS number	: 106-98-9		
Product code	: 001009		
Ingredient name		%	CAS number
but-1-ene		100	106-98-9

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact Inhalation	<ul><li>No specific data.</li><li>No specific data.</li></ul>
Over-exposure signs/syn	
Ingestion	: As this product is a gas, refer to the inhalation section.
Frostbite	: Try to warm up the frozen tissues and seek medical attention.
Skin contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Inhalation	: No known significant effects or critical hazards.
Eye contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Most important symptoms Potential acute health eff	/effects, acute and delayed ects
Ingestion	: As this product is a gas, refer to the inhalation section.
Skin contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. To avoid the risk of static discharges and gas ignition, soak contaminated clothing thoroughly with water before removing it. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.</li> </ul>

### Section 4. First aid measures

Ingestion

: No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

#### Section 5. Fire-fighting measures **Extinguishing media** Suitable extinguishing : Use an extinguishing agent suitable for the surrounding fire. media Unsuitable extinguishing : None known. media Specific hazards arising : Contains gas under pressure. Extremely flammable gas. In a fire or if heated, a from the chemical pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Hazardous thermal Decomposition products may include the following materials: t decomposition products carbon dioxide carbon monoxide **Special protective actions** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable for fire-fighters training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. If involved in fire, shut off flow immediately if it can be done without risk. If this is impossible, withdraw from area and allow fire to burn. Fight fire from protected location or maximum possible distance. Eliminate all ignition sources if safe to do so. Fire-fighters should wear appropriate protective equipment and self-contained breathing **Special protective** apparatus (SCBA) with a full face-piece operated in positive pressure mode. equipment for fire-fighters

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	Accidental releases pose a serious fire or explosion hazard. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Section 6. Accidental release measures

#### Methods and materials for containment and cleaning up

Small spill	: Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment.
Large spill	: Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

#### Precautions for safe handling **Protective measures** : Put on appropriate personal protective equipment (see Section 8). Contains gas under pressure. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage: do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement. Advice on general : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, occupational hygiene drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. Conditions for safe storage, : Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from including any incompatible materials (see Section 10). Eliminate all ignition sources. Keep container incompatibilities tightly closed and sealed until ready for use. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52 °C (125 °F).

### Section 8. Exposure controls/personal protection

#### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
but-1-ene	ACGIH TLV (United States, 3/2012). TWA: 250 ppm 8 hours.

Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

Date of issue/Date of revision       : 04/21/2015.       Date of previous issue       : 9/29/2014.       Version       : 0.04	5. Date of previous issue: 9/29/2014.Version: 0.04	: 04/21/2015. Date of previous issue	ate of issue/Date of revision : 04/21/2015.
-------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------	--------------------------------------	---------------------------------------------

## Section 8. Exposure controls/personal protection

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

### Section 9. Physical and chemical properties

<u>Appearance</u>						
Physical state	: Gas. [Compressed gas.]					
Color	: Colorless.	: Colorless.				
Molecular weight	: 56.11 g/mole					
Molecular formula	: C4-H8					
<b>Boiling/condensation point</b>	: -6.47°C (20.4°F)					
Melting/freezing point	: -185°C (-301°F)					
Critical temperature	: 419.4°C (786.9°F)					
Odor	: Odorless.					
Odor threshold	: Not available.					
рН	Not available.					
Flash point	: Closed cup: -80°C (-112°F)					
Burning time	: Not applicable.					
Burning rate	: Not applicable.					
Evaporation rate	: Not available.					
Flammability (solid, gas)	: Not available.					
Lower and upper explosive (flammable) limits	: Lower: 1.5% Upper: 9.3%					
Vapor pressure	: 23.5 (psig)					
Date of issue/Date of revision	: 04/21/2015. Date of previous issue	: 9/29/2014.	Version : 0.04	5/12		

#### 1-Butene

### Section 9. Physical and chemical properties

Vapor density	: 1.93 (Air = 1)
Specific Volume (ft <sup>3</sup> /lb)	: 6.8965
Gas Density (lb/ft <sup>3</sup> )	: 0.145 (25°C / 77 to °F)
Relative density	: Not applicable.
Solubility	: Not available.
Solubility in water	: 0.222 g/l
Partition coefficient: n- octanol/water	: 2.4
Auto-ignition temperature	: 385°C (725°F)
Decomposition temperature	: Not available.
SADT	: Not available.
Viscosity	: Not applicable.

### Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatibility with various substances	: Extremely reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Hazardous polymerization : Under normal conditions of storage and use, hazardous polymerization will not occur.

### Section 11. Toxicological information

#### Information on toxicological effects **Acute toxicity** Not available. Irritation/Corrosion Not available. **Sensitization** Not available. **Mutagenicity** Not available. **Carcinogenicity** Not available. Date of issue/Date of revision :04/21/2015. Date of previous issue : 9/29/2014. Version :0.04 6/12

## Section 11. Toxicological information

	biogical information
Reproductive toxicity Not available.	
Teratogenicity Not available.	
<u>Specific target organ toxici</u> Not available.	<u>ty (single exposure)</u>
Specific target organ toxici Not available.	<u>ty (repeated exposure)</u>
Aspiration hazard Not available.	
Information on the likely routes of exposure	: Routes of entry anticipated: Inhalation.
Potential acute health effects	<u>s</u>
Eye contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Ingestion	: As this product is a gas, refer to the inhalation section.
	vsical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
	cts and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
. Stanty should	

#### Numerical measures of toxicity

Date of issue/Date of revision: 04/21/2015.Date of previous issue: 9/29/2014.Version: 0.04
--------------------------------------------------------------------------------------------

### Section 11. Toxicological information

#### Acute toxicity estimates

Not available.

### Section 12. Ecological information

#### **Toxicity**

Not available.

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
but-1-ene	2.4	-	low

#### Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Empty ALL-GAS owned pressure vessels should be returned to ALL-GAS. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

### Section 14. Transport information

	DOT	TDG	Mexico	IMDG	IATA
UN number	UN1012	UN1012	UN1012	UN1012	UN1012
UN proper shipping name	Butylene (but-1-ene)				
Transport hazard class(es)	2.1	2.1	2.1	2.1	2.1
Packing group	-	-	-	-	-
Environment	No.	No.	No.	No.	No.

 Information
 Explosive Limit and Limited Quantity Index 0.125
 -</

"Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product."

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to Annex II of MARPOL 73/78 and the IBC Code

### Section 15. Regulatory information

: TSCA 8(a) CDR Exempt/Partial exemption: Not determined
United States inventory (TSCA 8b): This material is listed or exempted.
Clean Air Act (CAA) 112 regulated flammable substances: but-1-ene
: Not listed
n ingredients
: Not applicable.
: Fire hazard Sudden release of pressure
2

1-Butene							
Section 15. Regula	atory i	nformat	ion				
Name		%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
but-1-ene		100	Yes.	Yes.	No.	No.	No.
State regulations							
Massachusetts	: This r	naterial is liste	ed.				
New York	: This r	naterial is not	listed.				
New Jersey	: This r	naterial is liste	ed.				
Pennsylvania	: This r	naterial is liste	ed.				
Canada inventory	: This r	naterial is liste	d or exemp	oted.			
International regulations							
International lists	China Japa Korea Malay New 2 Philip	a inventory (II n inventory: T a inventory: T ysia Inventory Zealand Inve	ECSC): Thi This materia This materia (EHS Reg ntory of Ch ory (PICCS	s material is I al is listed or e al is listed or e gister): Not de nemicals (NZ 6): This mater	exempted. etermined. <b>IoC)</b> : This mat ial is listed or o	oted. terial is listed or	exempted.
Chemical Weapons Convention List Schedule I Chemicals	: Not lis	sted					
Chemical Weapons Convention List Schedule Il Chemicals	: Not lis	sted					
Chemical Weapons Convention List Schedule III Chemicals	: Not lis	sted					
<u>Canada</u>							
WHMIS (Canada)	Class CEPA Canac Canac Albert Ontar	io Designated	ole gas. Inces: This his material is material I Substanc I Substanc	is not listed. is listed. <b>es</b> : This mate <b>ces</b> : This mate	ot listed. erial is not liste erial is not liste erial is not liste	ed.	

## Section 16. Other information

	Class B-1: Flammable gas.		
lazardous Material Informat	<u>ion System (U.S.A.)</u>		
Health	0		
Flammability	4		
Physical hazards	3		

### Section 16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

#### National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

<u>History</u>	
Date of printing	: 04/21/2015.
Date of issue/Date of revision	: 10/15/2014.
Date of previous issue	: 9/29/2014.
Version	: 0.04
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United NationsACGIH – American Conference of Governmental Industrial Hygienists AIHA – American Industrial Hygiene Association CAS – Chemical Abstract Services CEPA – Canadian Environmental Protection Act CERCLA – Comprehensive Environmental Response, Compensation, and Liability Act (EPA) CFR – United States Code of Federal Regulations CPR – Controlled Products Regulations DSL – Domestic Substances List GWP – Global Warming Potential IARC – International Agency for Research on Cancer ICAO – International Agency for Research on Cancer ICAO – International Agency for Research on Cancer ICAO – International Civil Aviation Organisation Inh – Inhalation LC – Lethal concentration LD – Lethal dosage NDSL – Non-Domestic Substances List NIOSH – National Institute for Occupational Safety and Health

### Section 16. Other information

TDG – Canadian Transportation of Dangerous Goods Act and Regulations TLV – Threshold Limit Value

TSCA – Toxic Substances Control Act

WEEL – Workplace Environmental Exposure Level

WHMIS – Canadian Workplace Hazardous Material Information System

#### References

: Not available.

**V** Indicates information that has changed from previously issued version.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.